



All thicknesses for 6010SH purpose only



- | | |
|---|--|
| 1. 65mm sand cement screed | 8. Regupol® hi-tack tape or similar approved |
| 2. Taped joint* | 9. Acoustic sealant |
| 3. Min.500 gauge polythene | 10. Regupol SH perimeter strip |
| 4. Regupol® high tack tape | 11. Ceiling (construction type will vary) |
| 5. Regupol® 6010SH 10mm or 15mm layer | |
| 6. Pre-cast or beam and block floor, minimum 300kg/m ² | |
| 7. Acoustic cavity closer | |
- *DPM overlap to be minimum 100mm

Origin Underlay

Key Features

- Excellent impact and airborne performance
- Offers long term performance without collapse or “bottoming” out under high point loads
- Resistant to ageing and deformation
- Quick and easy to install
- High quality and exact material thickness guaranteed
- Mildew and moisture proof
- Accreditation to ISO 9001, ISO 14001 and ISO 18001
- Product manufactured using Recycled Materials and 100% recyclable

Warranty

The Origin Underlay is covered by a 7 year warranty against manufacturers defects. This does not include wear and tear.

Specification

| | |
|---------------------------------|---|
| SKU | OF-6010SP-6 |
| Size | 1250 x 2000mm |
| Bevel | No |
| Construction | Homogenous (single layer) |
| Material | SBR Rubber Sheet |
| Appearance | Coarse Open Face |
| Footfall Usage | Underlay Only |
| Installation | Bonded |
| Mean value of dynamic stiffness | 28.8MN/m ³ (DIN EN 29052-1) |
| Density | 595kg/m ³ |
| Tensile strength | approx 0.4N/mm ² |
| Thermal conductivity | approx 0.14W/mK |
| Elongation at break | approx 70% |
| Maximum load bearing capacity | 10,000kg/m ² (100kN/m ²) |
| Temperature resistance | -40°C to +110°C |
| Thickness | 6mm, 8mm or 10mm |

